

Data sheet

Climatic Chamber KK 500 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller: - large (7"), clear, full colour touch screen

- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download




Smart PRO - preview screen





A. POLOK – KOWALSKA, S. KOWALSKI 44-300 WODZISŁAW ŚLĄSKI, UL. KOKOSZYCKA 172 C

TECHNICAL DATA	
air convection	forced
chamber capacity [I]	462
working capacity [I]	392
controller	microprocessor PID
display	7" full colour touch screen
TEMPERATURE AND HUMIDITY	
temperature range [°C]	0+60
temperature resolution every [°C]	0,1
temperature variation at 25°C and 60%rH [+/-°C]*	2,0
relative humidity range [%]	3090 (see chart for details)
humidity resolution every [%]	1,0
humidity variation at 25°C and 60% rH [%rH]	5,0
over temperature protection	class 3.3 to DIN 12880




obszar pracy krótkotrwałej (max.24 h) short-term work area (max. 24h)

Wilgotność względna / Relative humidity [%]

CHAMBER	
door type	double (external solid, internal glass) / external glass (option)
interior	
Smart PRO	DIN 1.4301
IG Smart PRO	DIN 1.4301
housing	
Smart PRO	powder coated sheet
IG Smart PRO	stainless steel linen finish








overall dims [mm] /1/	
width A	660
height B	1990
depth C	1010
internal dims [mm]	
width D	470
width D'	510
height E	1510
depth F	600
height I	1360

tel. (+48) 32 453 91 70



shelves (standard max)	3 11
max shelf workload [kg] /2/	20
- reinforced shelf version (PW) [kg] /3/	100
max unit workload [kg]	100
weight [kg]	130

ELECTRICAL PARAMETERS		
voltage**	230V 50-60Hz	
nominal power [W]	1850	
refrigerant	R290 / GWP=3	
warranty	24 months	
manufacturer	POL-EKO-APARATURA	
txt_opis pod tabelą	all the above technical data refer to standard units (without optional accessories) * - variation (K) calculated for chamber as: K= +/- (T average max T average min.) / 2 ** - other power supplies on request 1 - depth doesn't include 50 mm of power cable 2 - on uniformly loaded surface 3 - reinforced shelf 4 - reinforced version	

all the above technical data refer to standard units (without optional accessories)

- * variation (K) calculated for chamber as: K= +/- (T average max. T average min.) / 2
- ** other power supplies on request
- 1 depth doesn't include 50 mm of power cable
- 2 on uniformly loaded surface
- 3 reinforced shelf
- 4 reinforced version

OPTIONS AND ACCESSORIES



Order number: */A

door with viewing window



Order number: */P INOX

Stainless steel wire shelf INOX

Bank: ING BŚ o/Wodzisław Śl. Nr rachunku: 90 1050 1403 1000 0022 0879 5498 Nr rej. W BDO 000005609







Order number: */PP Perforated shelf

tel. (+48) 32 453 91 70



Order number: */PW Reinforced shelf



Order number: KUW GN*/* Stainless steel cuvettes



Order number: */FIT Phytotron system



Order number: FIT/R3 FIT panels independent control



Order number: GNZ Internal socket



Order number: KK/CP Low water level sensor



Order number: BRT/*/L or IQ/OQ/PQ Calibration and IQ, OQ, PQ qualification



Order number: BPP 12 Battery backup for display



Order number: PORT ALARM Dry alarm contact



Order number: USBK USB cable



Order number: LANK LAN cable



Order number: OCZ/20 Non-standard access port 20 mm



Order number: OCZ/30 Additional access port 30 mm



Order number: OCZ/60 Non-standard access port 60 mm



Order number: OCZ/100 Non-standard access port 100 mm



Order number: KK/Z Container for deionised water





tel. (+48) 32 453 91 70

e-mail: info@pol-eko.com.pl internet: www.pol-eko.com.pl

POL-EKO-APARATURA SP. J.

A. POLOK – KOWALSKA, S. KOWALSKI 44-300 WODZISŁAW ŚLĄSKI, UL. KOKOSZYCKA 172 C

 $\Big(\!\!\big((\bullet)\!\big)\!\!\Big)$

Order number: KD Access control

(a)

Order number: CCTV Camera inside the chamber



Order number: CCTV CAM Additional camera

