

Low temperature oven **SNOL 60/300** is designed for thermal treatment of various materials up to 300°C. This electric oven is designed for treatments such as drying, heating, thermal testing, aging and similar purposes in an airflow environment. Forced air convection allows a homogeneous temperature distribution during the process, which ensures optimal results, moreover, good technical parameters ensure high-quality results. The oven can be used in scientific laboratories, educational institutions, medicine and industry.

DESCRIPTION

- ✓ Stainless steel (304) chamber,
- ✓ Adjustable forced horizontal air circulation,
- ✓ 3 stainless steel shelves,
- ✓ Insulation – rock wool (complete lack of asbestos),
- ✓ Outside casing – textured stainless steel,
- ✓ Door opening to the right, inner door in stainless steel, silicon joint,
- ✓ Buzzer,
- ✓ OTP – non-adjustable over temperature protection,
- ✓ Control panel is placed in the underpart of the oven,
- ✓ Non-programmable temperature controller – Omron E5CC,
- ✓ Short heating up / cooling down period,
- ✓ 2 year warranty.

Technical data	Units	Specifications
Useful volume	Liter	60
Rated power not more than	kW	2
Rated supply voltage	V	230
Rated frequency	Hz	50
Number of phases	-	1
Continuous operating temperature	°C	T+10-300
Maximum temperature	°C	300
Working chamber material	-	Stainless steel (304)
Working chamber surroundings	-	Air (with air fan)
Shelves	-	3/7
Maximum heating- up time (without charge),	Min.	34
Temperature stability in working chamber at rated temperature in thermal steady state without charge not more than	±°C	0.3
Temperature uniformity in working space at rated temperature in thermal steady state without charge not more than	±°C	2.0
Oven working chamber dimensions:		
width	mm	380
depth	mm	380
height	mm	420
Oven dimensions:		
width	mm	600
depth	mm	755
height	mm	720
Mass (Netto)	kg	49

CONTROL:

- ✓ Temperature measurement by thermocouple type "J".
- ✓ PID electronic regulator, double digital display reference temperature and measured temperature.
- ✓ Products are equipped with high-precision digital microprocessor Omron or Eurotherm temperature controllers fitted with self-tuning and manual PID settings. The customer can select a basic or programmable temperature controller, which offers up to 32 programming segments (rate of temperature rise or decrease control, maintenance of present temperature, automatic shutdown). A wide range of devices allows selecting the most appropriate controller for your process.
- ✓ SSR control unit.

SUPPLIED DOCUMENTS:

- ✓ Furnace and temperature controller instructions,
- ✓ Electric diagram

OTHERS:

- ✓ CE marked

PACKING:

- ✓ Wooden box

OPTIONS:

- ✓ Eurotherm 3216 (non-programmable)
- ✓ Eurotherm 3208 (programmable)
- ✓ Omron E5CC-T (programmable)
- ✓ PC connection and SNOL software
- ✓ OTP (over temperature protection, non-adjustable)
- ✓ OTP (over temperature protection, adjustable Eurotherm 3216i)
- ✓ OTP (over temperature protection, adjustable Omron E5GC)
- ✓ Timer (delayed furnace start)
- ✓ Gas injection system for Argon or Nitrogen (flowmeter, reducer and connections)+Semi-airtight chamber
- ✓ Additional hole with cover Ø50mm
- ✓ Semi-airtight chamber
- ✓ Window 258x200 mm
- ✓ Additional shelf
- ✓ Hardened shelf

WARRANTY:

- ✓ Two year limited warranty and later service for furnace.

COUNTRY OF ORIGIN:

- ✓ Lithuania (EU country)



Administrative address
Umega Group, AB
Metalo str.5, 28216 Utena
Lithuania

Factory address
Umega Group, AB, SnolTherm unit
Plento str.3, 28104 Utena
Lithuania

Tel. +370 389 54586
sales@snoltherm.com
www.snol.com

VAT code: LT263347219
Company registration No. 126334727